

CLEAN SLATE

ANTI GRAFFITI PAINT

Your trusted solution for a graffiti-free property.

Excellent Gloss Retention

Non-yellowing gloss retention. Extremely hard wearing with a durable finish. The anti graffiti membrane dries clear, maintaining the natural appearance of your surfaces without changing their look.

Protect your property with our anti-graffiti paint – effortless removal, long-lasting defense, and a cost-effective solution to keep your surfaces clean and pristine!

Highly Durable

Cohe's Clean Slate is a highly durable coating suitable for medium to heavy industrial applications with a significant reduction in VOC emissions. Clean Slate provides a long lasting barrier that resists graffiti, preventing damage to surfaces.

Cost Effective

Reduces the need for frequent repainting and maintenance, lowering overall upkeep costs. By acting as a protective layer, it helps preserve the integrity of your surfaces, avoiding costly repairs.



Graffiti can be removed as long after the offence as **48 hours** using just a citrus cleaner and a wet rag with minimal agitation.



Formulated and manufactured in New Zealand for harsh New Zealand conditions.



Cohe's *Clean Slate* Anti-Graffiti system is a water based polyurethane system designed for long lasting, easy graffiti removal.



Suitable for use on a **range of substrates** including concrete, block, tilt slab, brick, wood and metal.



Graffiti can be removed as long after the offence as **48 hours** using just a citrus cleaner and a wet rag with minimal agitation.



To remove graffiti on a Clean Slate surface, simply soak a rag in a citrus based cleaner and **wipe clean**.



Peace of mind to ensure your buildings are kept **graffiti free** maintaining a clean and professional appearance.

Physical Properties & Application Details.

Resin Type:	Aliphatic polyurethane/Aliphatic polyisocyanate
Pigmentation:	None
Colour:	Clear after drying
Gloss at 60° head:	>75% @ 60°
Specific gravity (kg/L):	1.2 - 1.4
Coverage (m ² /L):	6.0 per coat
No. of coats:	2 to 3
Dry times: (at 20°C and 60% RH):	3 hours (touch dry)
Recoat time:	4 hours, maximum 24 hours
Cure:	14 days (full hardness)
Pot life:	2 hours
Wet Film Thickness: 165?	(what is the unit here?)
Dry Film Thickness: 70 ?	(what is the unit here?)
Packaging Sizes:	4L + 10L
Thinner and clean up:	Water
Theoretical VOC (g/L):	32 g/L
Mix Ratio:	5:1 by weight

Cohe Anti-Graffiti System is a clear water reducible nontoxic coating. It is nonflammable and requires no specific handling. We recommend the use of a barrier cream or gloves for hands when applying.



Always request primer/preparation specification prior to each project application.

Please ensure you have a copy of the MSDS and review it thoroughly for safety procedures before use.

A project specification for primer, preparation details is required prior to application for all substrates.

Do not apply when the surface temperature is below 10°C or above 30°C. Do not apply when humidity is 88% or higher.



Call a Cohe technical expert on 0508 SEAL IT (732 548).